



HARP LUBRICANTS – TECHNICAL DATA SHEET

HARP VAC 235

(Vacuum pump oil)

HARP VAC235 is a very high quality vacuum pump oil with excellent thermal stability. The base oil is refined in such a way as to remove the aromatic hydrocarbons that are the unstable components and first to breakdown. It is then formulated to withstand the rigours of long operational running. HARP VAC235 is available in 0.95 litre and 3.79 litre package sizes.

HARP LUBRICANTS TECHNICAL DATA

Property/Characteristic	HARP VAC235	
	Method	Typical value
Viscosity:		
at 40°C (cSt)	D-445	46
at 100°C (cSt)		6.5
at 100°F (SUS)		230
at 210°F (SUS)		48
Viscosity Index	D-2270	99
Pour Point (°F)	D-97	10
Pour Point (°C)	D-97	-12
Colour ASTM	D-1500	<0.5
Flash Point, COC (°F)	D-92	470
Flash Point, COC (°C)	D-92	243
Specific gravity @ 60°F (15.6°C)	D-1298	0.8703
API Gravity	D-1298	31.0

VERSION 1 – jpd061207

Harp International Limited

Gellihirion Industrial Estate, Pontypridd, Rhondda Cynon Taff, CF37 5SX
United Kingdom

Telephone: +44 (0) 1443 842255
E-mail: harp@harpintl.com

Fax: +44 (0) 1443 841805
Web: <http://www.harpintl.com>